

# Eonis 24" (MDRC-2224 WP)

24" clinical display designed for infection control



This 24" Eonis® display has been built with healthcare specialists in mind. It combines consistent image quality and an attractive, versatile design with networked quality assurance. The white version display features a front glass panel and is fully sealed, making it exceptionally cleanable, even with 70% alcohol cleaning agents.

## Fully cleanable design

Barco's Eonis features toughened glass and covered cables, making the display safe to use in a clinical environment. In places where infection control is a major concern, the white version is the best choice. The display has a protective front glass panel and is rated IP-32 front and back, making it exceptionally cleanable to prevent contamination. The multiple mounting options and connections further add to the smart design.

## Consistent image quality

Barco's Eonis display has a unique front consistency sensor to automatically align the image quality every time the display is switched on. The image consistency makes collaboration between specialists easier. They can discuss images with colleagues at multiple locations, knowing that everyone is seeing identical images.

## Centralized quality assurance

The Eonis display comes complete with Barco's cloud-based MediCal QAWeb software, an online service for automated calibration, Quality Assurance and asset management. Praised in hospitals around the world, MediCal QAWeb allows healthcare IT and PACS administrators to centrally and remotely manage image quality across the healthcare organization, at the click of a button.

**BARCO**

Visibly yours

**Product specifications****Eonis 24" (MDRC-2224 WP)**

<b>Screen technology</b>	TFT Color LCD IPS
<b>Active screen size (diagonal)</b>	611.3 mm (24.1") 518.4 mm x 324.0 mm (20.41" x 12.76") (HxV)
<b>Backlight</b>	LED
<b>Aspect ratio</b>	16:10
<b>Resolution</b>	2MP (1920 x 1200)
<b>Pixel pitch</b>	0.270 mm x 0.270 mm
<b>Color imaging</b>	Yes
<b>Gray imaging</b>	Yes
<b>Color support</b>	10 bit; 16.7 million colors
<b>Viewing angle</b>	178° (IPS)
<b>Ambient Light Compensation (ALC)</b>	Yes, preset values in OSD
<b>Front sensor</b>	Yes
<b>Maximum luminance</b>	300 cd/m <sup>2</sup> typical
<b>DICOM calibrated luminance</b>	180 cd/m <sup>2</sup>
<b>Contrast ratio</b>	1000:1 typical
<b>Response time (Tr + Tf)</b>	14 ms typical
<b>Housing color</b>	White + Silver
<b>Video input signals</b>	VGA, DisplayPort, HDMI
<b>USB ports</b>	1 upstream, 2 downstream
<b>USB standard</b>	2.0
<b>Power requirements (nominal)</b>	100-240 V
<b>Power consumption (nominal)</b>	40 W (less than 1.0 W in stand-by)
<b>Power save mode</b>	Yes
<b>Power management</b>	DPMS
<b>Dot clock</b>	165 MHz
<b>OSD languages</b>	English, French, German, Spanish, Italian, Dutch, Japanese, Traditional Chinese, Simplified Chinese, Korean
<b>Dimensions with stand (W x H x D)</b>	560.4 x 533 x 166.35 mm
<b>Dimensions w/o stand (W x H x D)</b>	560.4 x 366 x 61.72 mm
<b>Dimensions packaged (W x H x D)</b>	481 x 273 x 761 mm
<b>Net weight with stand</b>	9.5 kg
<b>Net weight w/o stand</b>	6.17 kg
<b>Net weight packaged with stand</b>	13.5 kg
<b>Height adjustment range</b>	100 mm +/- 5.0 mm
<b>Tilt</b>	-5° / +20°
<b>Swivel</b>	-45° / +45°
<b>Pivot</b>	90°
<b>Mounting standard</b>	VESA (100 mm)
<b>Screen protection</b>	Protective, non-reflective glass cover
<b>Certifications</b>	CE (MDD 93/42/EEC class I product), CE-2004/108/EC, 2014/30/EU (Directive 2004/108/EC is repealed with effect from 20 April 2016), IEC 60601-1 (ED.3), ANSI/AAMI ES60601-1 (2005 + C1:09 + A2:10), CAN/CSA-C22.2 No. 60601-1:08, DEMKO - EN 60601-1:2006, EN 60601-1-2:2007, EN 60601-1:2006+A11:2011, KC, VCCI, FCC class B, ICES-001 Level B, FDA Class I device, RoHS

**Product specifications**

**Eonis 24" (MDRC-2224 WP)**

**Supplied accessories**

User Guide  
Cable routing strap  
Video cables (1 x VGA + 1 x HDMI + 1 x DP)  
Main cables (UK, European (CEBEC/KEMA) or USA (UL/ CSA; adaptor plug NEMA 5-15P) or Chinese (CCC))  
USB 2.0 cable  
This adapter(s) is a forming part of the medical device.(Manufacturer: BridgePower Corp.; model:BPM060S12F03; Input:100-240 V AC, 50-60 Hz, 1.5 A; Output: +12V DC ( ), 5.0 A)

**QA software**

QAWeb & QAWeb Private Practice

**Warranty**

3 years